



# Technical Bulletin and Application Guideline

Page: 1 of 1  
November 2003

## **BOMANITE POLY FABRIC**

### **PRODUCT DESCRIPTION**

#### **A) Composition and Typical Uses**

Bomanite Poly Fabric is an alkaline resistant polypropylene woven-mesh fabric designed to reinforce Bomanite Waterproofing Membrane, Bomanite Crack Repair Kit and Micro-Top. Bomanite Poly Fabric adds strength and serves as a control to ensure proper application thickness. It also provides additional reinforcement over cracks and joints.

Bomanite Poly Fabric is used in waterproof membranes and cementitious coatings beneath ceramic tile, marble, quarry tile, latex mastic surfacing and certain types of between-slab or below-grade membranes.

#### **B) Advantages**

- Adds strength
- Provides crack resistance
- May be embedded with liquid applied waterproofing membranes or cementitious coatings

#### **C) Packaging**

Bomanite Poly Fabric is packaged in 40-inch wide by 300-foot long rolls (1,000 sq. ft.).

### **SPECIFICATION ASSISTANCE**

Consult Bomanite Corporation for specification assistance, detailing, etc. This consultation is highly recommended prior to specification.

### **WARRANTY**

This product is warranted to meet uniform quality standards within conventional manufacturing tolerances. Since no control is exercised over product use, no warranty or guarantee, expressed or implied, can be made to its use. Seller's and manufacturer's obligation under this warranty is limited to reimbursement of the purchase price of the portion of the product proven to be defective. The user assumes all risks and liability resulting from the use of this product.